

ICONIK 320

TECHNICAL DATA VINYL FLOORING 2020

Classification	Norm	Tarkett Value
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering Reinforced with a calendared interlayer
Domestic classification	EN ISO 10874	23/31 Domestic Heavy/Commercial Moderate
Binder content	ISO 11638	Type I
Technical characteristics		
Total thickness	ISO 24346	3.2 mm
Wear layer thickness	ISO 24340	0,30 mm
Total weight	ISO 23997	2.300 g/m ²
Roll Width		4 + 2 + 3 m
Roll Length	EN ISO 24341	24 m
Performance for CE Marking		
Declaration of Performance #	EN 14041	0132-0067-DOP-2020-01
Reaction to fire	EN 13501-1	Bfl-s1
Slip resistance	EN 13893 DIN 51130	> 0,30 R 10
Electrostatical propensity	EN 1815	< 2 kV
Thermal resistance (in m ² ·K/W)	ISO 10456 / EN 12524-1	0,03
Formaldehyde emission	EN 717-1	E1
Technical Performance		
Impact sound reduction - ΔLw	EN ISO 717-2	18 dB
Residual indentation	ISO 24343-1	< 0.20 mm
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (maximum 27°C)
Colour fastness to light	ISO 105-B02	≥ 6
Dimensional stability	ISO 23999	≤ 0,20 %
Castor Chair	ISO 4918	OK
Sustainability, Environment & Indoor Air Quality		
Recyclable		Yes
French VOC rating		A+
Phthalate content		Phthalate-free
TVOC emissions after 28 days	EN 16516	Gold (≤ 100 µg / m ³)
Product ID		
Residential warranty (in years)		15
Surface treatment		Extreme Protection

The above information is subject to modification for the benefit of further improvement (2020-01).

