

Ruby 70

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Binder content	ISO 10582	Type I
Technical Characteristics	Norm	Tarkett Value
Wear layer thickness	EN ISO 24340	0,70 mm
Total thickness	EN ISO 24346	2 mm
Total weight	EN ISO 23997	3000 g/m ²
Surface treatment		Top Clean
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0131-0038-DoP-2014-10
Reaction to fire	EN ISO 13501-1	Bfl-s1
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN ISO 10456	0,020 m ² •K/W
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,10 mm
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 %
Slip resistance	DIN 51130	R10
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Curly resultant to heat	EN ISO 23999	≤ 8 mm
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Recycled content		31 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		6,83 kg CO ₂ eq /m ²
Total VOC Emissions	EN 16516	Gold (≤ 100 µg / m ³)
Formaldehyde emission	EN 717-1	E1
Dimensions and designs		
Roll		Roll 2 x 23 m Roll 4 x 23 m
Number of designs available		32



The above information is subject to modification for the benefit of further improvement (30/01/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for the instructions.