

# Topaz 70

## Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 11638	Heterogeneous poly(vinyl chloride) flooring on foam (ISO 11638)
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Binder content	EN ISO 11638	Type I
Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2.50 mm
Total weight	ISO 23997	2900 g/m <sup>2</sup>
Wear layer thickness	ISO 24340	0.70 mm
Surface treatment		TopClean
Performance for CE Marking	Norm	Tarkett Value
UKCA - DoC certificate		0131-0022-DoC-2022-06
Declaration of Performance	EN 14041	0132-0022-DoP-2023-01
Reaction to fire	EN 13501-1	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) and/or Cf-s1 glued over any derivate wood substrate
Electrical Propensity	EN 1815	Antistatic ( $\leq 2$ kV)
Thermal resistance (m <sup>2</sup> K/W)	ISO 10456	0,020 m <sup>2</sup> •K/W
Slip resistance	EN 13893	Class DS ( $\mu \geq 0.30$ )
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	$\leq 0.10$ mm
Impact sound reduction - $\Delta Lw$	EN ISO 717-2	14 dB
Drum sound class	NF S31-074	B
Slip resistance	DIN 51130	R10
Furniture leg effect	EN 424	No damage
Castor chair effect	ISO 4918	No damage
Colour fastness to light	ISO 105-B02	$\geq 6$
Dimensional stability	EN ISO 23999	$\leq 0,10$ %
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Seam Strength Individual Value	EN 684	$\geq 240$ N/50mm
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Total recycled content		16 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		6.83 kg CO <sub>2</sub> e /m <sup>2</sup>
TVOC emissions after 28 days	EN 16516	Gold
Formaldehyde emission		E1
Dimensions and designs		
Roll		Roll 2x24m Roll 3 x 24 m Roll 4 x 24 m
Number of designs available		30



The above information is subject to modification for the benefit of further improvement (23/02/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.