

iD INSPIRATION LOOSE-LAY

TECHNICAL DATA

Classification	Standards	iD Inspiration Loose-Lay
Classification	EN ISO 10582:2010	Heterogeneous PVC Compact floor covering
	EN ISO 10874	Commercial: 33 Industrial: 42
Wear layer binder content	EN ISO 10582	Type I
Technical characteristics		
Total thickness	EN ISO 24346	4,5 mm
Wear layer thickness	EN ISO 24340	0,55 mm
Total weight	EN ISO 23997	7500 g/m ²
Bevelled edges	-	Yes - 4 bevels on 3 references
Surface treatment (PUR)	-	Yes - TopCleanXP™
Form of delivery	EN ISO 24342	
	Planks	22,90 x 121,90 cm 10 planks/box (= 2.79 m ²), 52 boxes/pallet (= 145.16 m ²) 25,4 x 152,4 cm 6 planks/box (= 2.32 m ²), 52 boxes/pallet (= 120.74 m ²)
	Tiles	30,50 x 61 cm 14 tiles/box (= 2.6 m ²), 54 boxes/pallet (= 140.65 m ²) 60 x 60 cm 8 tiles/box (=2.88 m ²), 40 boxes/pallet (= 115.20 m ²)
Performance for CE marking requirement (EN 14041)		
Declaration Of Performance	EN 14041	0131-0055-DoP-2015-01
Reaction to fire	EN 13501-1	B _{fl} -s1 loose laid on wood panel and A2 _{fl} -s1 or A1 _{fl} class substrate
Electrostatic properties	EN 1815 EN 1081	<2 kV on concrete > 10 ⁹ Ohm
Thermal resistance	EN ISO 10456	0,04 m ² K/W
Antislip classification	EN 13893	μ ≥ 0.30
Technical performances		
Dimensional stability	EN ISO 23999	≤ 0,10%
Curl resultant to heat	EN ISO 23999	≤ 1 mm
Impact sound reduction	EN ISO 717-2	ΔLw = 8 dB
Slip resistance	DIN 51130	R9
Furniture leg	EN 424	No damage
Castor chair	ISO 4918	No damage
Light fastness	EN ISO 105-B02	≥ 6
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Chemical resistance	EN ISO 26987	Very good
Underfloor heating	-	Suitable - max. 27 °C
Environmental performances		
Total VOC emission	ISO 16000-9	<100 μg/m ³
Recyclable	-	100%
Plasticizer	-	Phthalate-free

The above information is subject to modification for the benefit of further improvement. (11/18).

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for these instructions.

Customs Tariff: 4820 5000



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

