

Fusion | WL - Weaving latex

ege

Produkt beskrivelse



Fusion | WL - Weaving latex



Produkt beskrivelse



BESKRIVELSE	METHODE	DATA
KONSTRUKTION		
STRUKTUR	ISO 2424	Vævet loop pile
LUVMATERIALE	DIR 96/73, 96/74	Regenerated and regenerable PA
FARVEMETODE	-	Forfarvet garn
BAGSIDE	ETL	WL - Weaving latex
DIMENSIONER	ISO 3018	Approx. 400/500 cm
TOTALHØJDE	ETL	Ca. 5,3 mm.
TOTALVÆGT	ISO 8543	Ca. 2.125 g/m ²
LUVINDSATSVÆGT	ETL	285 g/m ²
EGNETHEDSPRØVNINGER		
BRUGSOMRÅDER	ETL	23 - Bolig - Kraftig brug
GARANTI	ETL	Garanti mod gennemslid 10 år
TRAPPEEGNET	ETL	Ja
ANTISTATISKE EGENSKABER	ETL	Permanent antistatisk
TRINLYDSDÆMPNING	ETL	17 dB
ISOLERINGSEVNE	ETL	Ca. 0,09 m ² K/W
SIKKERHED & MILJØ		
BRANDKLASSIFIKATION	EN 14041	Efl
	BS EN 14041	Efl
CE MÆRKNING	EN 14041	Certificeret
	Ydeevnedeklaration	DOP E
	Notified body no.	NA
	Ce Year	20
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
VEJLEDNINGER		
MONTERING, INKL. LIMGUIDE	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Français
RENGØRING, PLETFJERNING	DK	Dansk

Fusion | WL - Weaving latex



Produkt beskrivelse

BESKRIVELSE	METHODE	DATA
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

PRODUCENT

FABRIKSCERTIFICERING	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK