

Kingston | WL - Weaving latex

ege

Produkt beskrivelse



Produkt beskrivelse



BESKRIVELSE	METHODE	DATA
KONSTRUKTION		
STRUKTUR	ISO 2424	Vævet loop pile
LUVMATERIALE	DIR 96/73, 96/74	100% uld
FARVEMETODE	-	Forfarvet garn
BAGSIDE	ETL	WL - Weaving latex
DIMENSIONER	ISO 3018	Approx. 400/500 cm
TOTALHØJDE	ETL	Ca. 7,0 mm.
TOTALVÆGT	ISO 8543	Ca. 2.600 g/m2
LUVINDSATSVÆGT	ETL	625 g/m2
BIOCIDAL TREATMENT	Biocidal Product Regulation	Contains preservative to control
EGNETHEDSPRØVNINGER		
BRUGSOMRÅDER	EN 1307	23 - Bolig - Kraftig brug
GARANTI	ETL	Garanti mod gennemslid 5 år
ANTISTATISKE EGENSKABER	ETL	Permanent antistatisk
TRINLYDSDÆMPNING	ETL	30 dB
ISOLERINGSEVNE	ETL	Ca. 0,12 m2K/W
SIKKERHED & MILJØ		
BRANDKLASSIFIKATION	EN 14041	Efl
CE MÆRKNING	EN 14041	Certificeret
	Ydeevnedeklaration	DOP E
	Notified body no.	NA
	Ce Year	17
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
VEJLEDNINGER		
MONTERING, INKL. LIMGUIDE	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Français
RENGØRING, PLETFJERNING	DK	Dansk
	N	Norsk
	S	Svensk

Kingston | WL - Weaving latex



Produkt beskrivelse

BESKRIVELSE	METHODE	DATA
	GB	English
	D	Deutsch
	F	Francais

PRODUCENT

FABRIKSCERTIFICERING	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK